

HK Series Full Colour Indoor Fixed Installation Led Display

Application	Indoor							
Product Model	HK121	HK151	HK161	HK181	HK201	HK251	HK301	HK401
Pixel Pitch	1.25mm	1.538mm	1.667mm	1.86mm	2.0mm	2.5mm	3.076mm	4.0mm
Module Size	320X160mm	320X160mm	320X160mm	320X160mm	320X160mm	320X160mm	320X160mm	320X160mm
Module Resolution	256X128	208X104	192X96	172X86	160X80	128X64	104X52	80X40
Led	SMD1010	SMD1212	SMD1212	SMD1515	SMD1515	SMD2020	SMD2020	SMD2020
Cabinet Size	640X480mm	640X480mm	640X480mm	640X480mm	640X480mm	640X480mm	640X480mm	640X480mm
Cabinet Resolution	512X384	416X312	384X288	344X258	320X240	256X192	208X156	160X120
Cabinet Weight	7.5KG	7.5KG	7.5KG	7.5KG	7.5KG	7.5KG	7.5KG	7.5KG
Pixel Density	409600pixel/m ²	409600pixel/m ²	409600pixel/m ²	262144pixel/m ²	147456pixel/m ²	112896pixel/m ²	65536pixel/m ²	43264pixel/m ²
Recommended Viewing Distance	≥1.2m	≥1.5m	≥1.6m	≥1.8m	≥2m	≥2.5m	≥3m	≥4m
Brightness	600cd/m ²	600cd/m ²	600cd/m ²	800cd/m ²	800cd/m ²	800cd/m ²	1000cd/m ²	1000cd/m ²
Max. Viewing Angle	Horizontal 160° Vertical 160°				Horizontal 140° Vertical 140°	Horizontal 140° Vertical 140°	Horizontal 140° Vertical 140°	Horizontal 140° Vertical 140°
Cabinet Material	Die-casting Aluminum							
Maintenance	Front							
Refresh Rate	≥3840HZ							
Grey Level	14bit							
Input Voltage	220~240VAC							
Max. Power Consumption	≤500W/m ²							
Ave. Power Consumption	≤200W/m ²							
Ingress Protection	IP30							
LED Life Time	≥100,000 hours							
Input	VGA DVI HDMI SDI							

Note: Specifications are subjected to change without notice.

SHENZHEN HONOURLED CO., LTD

Address: Building B1, Zone B, Phase II, Longfa Road Commercial Center, Longyuan Community, Longhua Street, Longhua District, Shenzhen

Tel: +86 198 0657 6268

Email: info@honourled.com