

HONOURLED

HO Series Full Colour Outdoor Fixed Installation Led Display

Product Model	1000mm x 1000mm Panel			960mm x 960mm Panel				
	HO390	HO480	HO620	HO440	HO570	HO660	HO800	HO100
Pixel Pitch	3.91mm	4.81mm	6.25mm	4.44mm	5.71mm	6.67mm	8.0mm	10mm
Module Size	500X250mm	500X250mm	500X250mm	480X320mm	480X320mm	480X320mm	480X320mm	480X320mm
Module Resolution	128X64	104X52	80X40	108X72	84X56	72X48	60X40	48X32
Led	SMD1415	SMD1415	SMD2727	SMD1415	SMD2727	SMD2727	SMD3535	SMD3535
Cabinet Size	1000x1000mm	1000x1000mm	1000x1000mm	960x960mm	960x960mm	960x960mm	960x960mm	960x960mm
Cabinet Resolution	256x256	208X208	160x160	216X216	168X168	144X144	120x120	96x96
Cabinet Weight	28KG	28KG	28KG	26KG	26KG	26KG	26KG	26KG
Pixel Density	65536pixel/m ²	43264pixel/m ²	25600pixel/m ²	50625pixel/m ²	30625pixel/m ²	22500pixel/m ²	15625pixel/m ²	10000pixel/m ²
Recommended Viewing Distance	≥3.9m	≥4.8m	≥6.2m	≥4.4m	≥5.7m	≥6.6m	≥8m	≥10m
Brightness	5500cd/m ²	5500cd/m ²	5500cd/m ²	5500cd/m ²	5500cd/m ²	5500cd/m ²	5500cd/m ²	5500cd/m ²
Max. Viewing Angle	Horizontal 140° Vertical 140°							
Cabinet Material	Aluminum							
Maintenance	Front&Rear							
Refresh Rate	≥3840HZ							
Grey Level	14bit							
Input Voltage	220~240VAC							
Max. Power Consumption	≤600W/m ²							
Ave. Power Consumption	≤240W/m ²							
Ingress Protection	IP65							
LED Life Time	≥100,000 hours							
Input	VGA DVI HDMI SDI							

Note: Specifications are subjected to change without notice.

SHENZHEN HONOURLED CO., LTD

Address: Building B1, Zone B, Phase II, Longfa Road Commercial Center, Longyuan Community, Longhua Street, Longhua District, Shenzhen

Tel: +86 198 0657 6268

Email: info@honourled.com